



Industrial Chemicals & Resins Co. LLC

Nx-4 Poly Vinyl Acetate Homo Polymer

Principal Properties:

- Excellent quality plasticized Homo Polymer.
- Excellent adhesion and binding power.
- Outstanding compatibility with other natural and synthetic adhesives.
- Suitable for both manual as well as machine application.
- Super clarity of dry film.

Applications:

General purpose wood adhesive for Teak, Plywood, Rexene, Cloth and Superior quality furnishers.

Product Data:

| | |
|--|------------------------|
| Viscosity @ 20°C (Brookfield DVE, spindle 7 @ 10 rpm) | 1,400 – 1,800 Poise |
| Solid content | 50±1 % |
| pH | 4 - 5 |
| Drying Time | 13 sec |
| Density @ 20°C | 1.11 g/cm ³ |
| Minimum film formation temperature | 9 °C |

Packing:

Nx 4 is supplied in 200 Kg open top steel drums.

Safety:

Due attention should be given to the precautions for handling chemicals provided in our Material Safety Data Sheet.

Remarks

The information submitted in this publication is given in good faith but without warranty, In view of the many factors that may affect the application, users are recommended to carry out their own trials to determine the suitability of the product for their practical requirements. We cannot accept responsibility for any damage or loss resulting from the use of this information.

B 882, Jebel Ali Industrial Area II, P.O Box 34398 Dubai. UAE

Tel . + 9714 8801516 Fax. + 9714 8801192

Email: icr@nimir.com