



## Nimir Specialty Chemicals FZE

### **INO-COAT HP**

Poly Vinyl Acetate  
Homo Polymer

#### **Principal Properties:**

- Excellent quality plasticized Homo Polymer.
- Excellent adhesion and binding power.
- Outstanding compatibility with other natural and synthetic adhesives.
- Suitable for both manual as well as machine application.
- Super clarity of dry film.

#### **Applications:**

General purpose adhesive for  
Teak, Plywood, Rexene, Cloth and Superior quality furnishers.

#### **Product Data:**

Viscosity @ 20°C (Brookfield DVE, spindle 7 @ 10 rpm)	800 -1,200 Poise
Solid content	50±1 %
pH	4 - 5
Drying Time	< 3 minutes
Density @ 20°C	1.11 g/cm <sup>3</sup>
Minimum film formation temperature	9 °C

#### **Packing:**

INO-COAT HP is supplied in 200 Kg open top steel drums.

#### **Safety:**

Due attention should be given to the precautions for handling chemicals provided in our Material Safety Data Sheet.

#### **Remarks:**

The information submitted in this publication is given in good faith but without warranty, In view of the many factors that may affect the application, users are recommended to carry out their own trials to determine the suitability of the product for their practical requirements. We cannot accept responsibility for any damage or loss resulting from the use of this information.