



Nimir Specialty Chemicals FZE

INO-COAT PA 398

Pure Acrylic Emulsion

Principal Properties:

- Versatile Pure Acrylic Emulsion specially engineered for various paint applications.
- High pigment binding capability.
- Excellent Scrub resistance.
- Excellent freeze-thaw and mechanical stabilities.
- Good leveling and flow properties.
- Unique stabilizing and easy penetration of polymer to the surface.
- Excellent Brush-ability

Fields of Applications:

INO-COAT PA 398 can be formulated into many types of paints, resulting in the coatings with excellent long term durability and resistance to UV radiation and can be used in:

- Indoor paints
- Textured Finishes.
- Silky Finishes.
- Soft and soothing effects

Product data:

Viscosity @ 25°C (Brookfield DVE, spindle 4 @ 30 rpm)	200-600 cps
Specific Gravity	1.03 – 1.05
pH	8.0 ± 1
Solid content	50%±1
Minimum film formation temperature	10 - 20°C
Particle Size µm	0.10 – 0.15
Film Characteristics	Milky White

Packing:

INO-COAT PA 398 is supplied in 200 Kg open top drums.

Safety:

Due attention should be given to the precautions for handling chemicals provided in our Material Safety Data Sheet.

Remarks:

The information submitted in this publication is given in good faith but without warranty, In view of the many factors that may affect the application, users are recommended to carry out their own trials to determine the suitability of the product for their practical requirements. We cannot accept responsibility for any damage or loss resulting from the use of this information.

Plot No. 1D-03, P.O Box 41671 – Hamriyah Free Zone – Sharjah. UAE
Tel. + 971-6-5263922 Fax. + 971-6-5263923 Email: nsc@nimir.com